

CIRCUIT BREAKER FINDER WITH NCV MS5905RTA / RTB / RTC / RTD / RTE

Specifications		MS5905RT				
Specifications		A	B	C	D	E
MS5905R+T	Quickly and Easily Identify if Individual Branch Circuits Work with MS5905T without Disrupting Power.	●	●	●	●	●
MS5905R Built-in Non-Contact Voltage Detector(NCV)	Voltage Range: AC90V~AC600V Frequency: 50Hz~60Hz Detecting Distance: <30mm	●	●	●	●	●
Work Light at the Head of MS5905R Pointing to the Target area.		●	●	●	●	●
Low Battery Indication		●	●	●	●	●
Operating Temperature and Humidity	0~50 <80%RH	●	●	●	●	●
Socket Tests			●	●	●	●
GFCI			●			
Buzzer and LED instructions		●	●	●	●	●




Specifications		MS5905RT	
General			
Power Supply	1x9V 6F22 Battery		
Product Size	MS5905R	177mm×46mm×31mm	6.97"×1.81"×1.22"
	MS5902TA	73mm×43mm×30mm	
	MS5902TB	2.87"×1.69"×1.18"	
	MS5902TC	71mm ×64mm×55mm	
	MS5902TD	2.8"×2.5"×2.16"	
	MS5902TE		
Product Weight	MS5902R	130g/0.29lb	
	MS5902TA	35g/0.9lb	
	MS5902TB		
	MS5902TC		
	MS5902TD	63g/0.14lb	
	MS5902TE		
Safety Rating	MS5902R	CAT II 600V	
	MS5902T	CAT II 125V	

● Feature Difference





MS5905RTA





MS5905RTB





GFCI



MS5905RTC



MS5905RTD



MS5905RTE

