


Rail Mounted Terminal Blocks : Polyamide Range Of Terminals : Fuse Terminal : KUDF 4



Type of Connection	MS Screw Clamp
Insulating Material	Polyamide 66
Terminal Pitch	8 mm (0.31 Inch)
Terminal Width	58 mm (2.26 Inch)
Terminal Height	42.5 mm (1.66 Inch)
Rated Cross Section	4 sq mm
Wire Stripping Length	9 mm
Screw Size	M3

Connection Possibility

Stranded wire	Max : 4 sq mm	Min : 0.5 sq mm
Solid wire	Max : 4 sq mm	Min : 0.5 sq mm

Ratings	IEC	UL
Voltage	800 V	600 V
Current	6.3 A	7 A
Conductor Size	4 sq mm	Min : 20 AWG Max : 12 AWG
Tightening Torque	0.4 Nm	6 Lbln

Terminal Accessories

Partition Plate With Foot	KBZF
End Clamp	SCUN, SCUSL, SCUDD, SCKN, DCKN
Comb-type Shorting Link	UFSL - 2W
Marking Label	LABEL KN8
Group Marking Carrier	SCKNMLH, SCUNMLH, DCKNMLH
Terminal Colours	GREY, KHAKHI, RED, YELLOW, BLUE, BLACK, GREEN
Mounting Channel	CHS10, CHK10, CHS3, CHS5, CHK5, CHK3, CHKS3, CHKS5, CHKS10, CHKDS10, CHKD10