

Rail Mounted Terminal Blocks : Polyamide Range Of Terminals : Distribution Block : FDBK 8



Type of Connection	MS Screw Clamp
Insulating Material	Polyamide 66
Terminal Pitch	55.5 mm (2.16 Inch)
Terminal Width	42.5 mm (1.66 Inch)
Terminal Height	46.5 mm (1.81 Inch)
Rated Cross Section	[IC-4 , OG-4] sq mm
Wire Stripping Length	12 mm
Screw Size	M3

Connection Possibility

Stranded wire	Max : 4 sq mm	Min : 0.5 sq mm
Solid wire	Max : 6 sq mm	Min : 0.5 sq mm

Ratings	IEC	UL
Voltage	800 V	600 V
Current	32 A	35 A
Conductor Size	[IC-4 , OG-4] sq mm	Min : [IC-20 , OG-20] AWG 10] AWG Max : [IC-10 , OG-
Tightening Torque	0.5 Nm	7 Lbln

Terminal Accessories

Partition Plate Without Foot	KBX
Partition Plate With Foot	KBXF
End Clamp	SCUN, SCUSL, SCUDD, SCKN, DCKN
Marking Label	LABEL KN6.5
Group Marking Carrier	SCKNMLH, SCUNMLH, DCKNMLH
Terminal Colours	GREY, KHAKHI, RED, YELLOW, BLUE, BLACK, GREEN
Mounting Channel	CHS10, CHK10, CHS3, CHS5, CHK5, CHK3, CHKS3, CHKS5, CHKS10, CHKDS10, CHKD10