



Drawing 9.1

No.	Model of fuse link				Rated voltage (V)	Rated current (A)	Weight (g)	Drawing No.	Overall dimension (mm)
	The company		Domestic and oversea similar products						
	General (gG)	Quick speed (aR)	General (gG)	Quick speed (aR)					
0901	RO06	RS06	-	-	250/380	1-32	6.5	9.1	φ 12.7 x 29
0902	RO07	RS07	-	-	600	10-100	7.5	9.1	φ 30 x 57
0903	RO09	RS09	-	-	500	2-63	17.4	9.1	φ 18 x 37
0904	RO10	RS10	-	-	500	2-63	23.5	9.1	φ 18 x 50
0905	RO11	RS11	AJT JKS LPJ	ACL	600	2-32	51.5	9.1	φ 21 x 58
0906	RO12	RS12	AJT JKS LPJ	ACL	600	35-100	90	9.1	φ 27 x 60
0907	RO13	RS13	-	-	500	2-40	23.2	9.1	φ 15 x 50
0908	RO14	RS14	RT19-16 gF1	-	500	0.5-20	4.4	9.1	φ 8.5 x 31.5
0909	RO14A	RS14A	-	-	250	0.5-20	3.5	9.1	φ 8.5 x 23
0910	RO14B	RS14B	-	-	380/500	0.5-20	5.0	9.1	φ 8.5 x 36
0911	RO15	RS15	RT14-20 gF2 RT18-32 RT19-25	KTK KLM	380/500	0.5-32	7.7	9.1	φ 10.3 x 38
0912	RO15A	RS15A	-	-	250	0.5-16	4.8	9.1	φ 10.3 x 25.8
0913	RO15B	RS15B	-	-	250/500	0.5-25	5.8	9.1	φ 10.3 x 31.5
0914	RO15C	RS15C	-	-	380/500	0.5-32	6.2	9.1	φ 10.3 x 34
0915	RO15D	RS15D	-	-	600	2-32	11	9.1	φ 10.3 x 57
0916	RO16	RS16	RT14-32 gF3 RT18-63 RT19-40	EWP	380/660	2-50	20.5	9.1	φ 14.3 x 51
0917	RO16A	RS16A	-	-	500	2-50	15.6	9.1	φ 14.3 x 38
0918	RO16B	RS16B	-	-	500	2-50	18.5	9.1	φ 14.3 x 45
0919	RO16C	RS16C	-	-	500	2-50	27.5	9.1	φ 14.3 x 67
0920	RO17	RS17	RT14-63 gF4 RT18-125 RT19-100	URE2263	380/660	10-125	58	9.1	φ 22.2 x 58
0921	RO18	RS18	-	-	380	0.5-25	4.8	9.1	φ 9.6 x 30
0922	RO19	RS19	FRS TRS FLSR	-	600	0.5-32	91.2	9.1	φ 20.5 x 127
0923	RO19A	RS19A	FLNR PC2	-	250/500	0.5-63	63	9.1	φ 20.5 x 76
0924	RO19B	RS19B	-	-	600	0.5-32	85	9.1	φ 20.5 x 114
0925	RO19C	RS19C	FRS TRS FLSR	-	600	32-63	172.4	9.1	φ 27 x 139
0926	RO19D	RS19D	-	-	600	32-63	160	9.1	φ 27 x 147
0927	RO54	RS54	-	-	250	0.5-16	1	9.1	φ 5 x 20
0928	RO55	RS55	-	-	250	0.5-16	1.3	9.1	φ 5 x 25
0929	RO56	RS56	-	-	250	0.5-16	1.7	9.1	φ 6 x 20
0930	RO57	RS57	-	-	250	0.5-16	2.1	9.1	φ 6.3 x 25
0931	RO58	RS58	-	-	250/500	0.5-16	2.5	9.1	φ 6.3 x 31.5

□ Characteristic Curve

