Wi-Fi Doorbell LTK6112-WIFI

Video Solutions for Security Professionals^T



- Max.5-meter IR distance
- Support wi-fi
- Support Motion dectection
- IP 55 standard
- Pairing Max units up to 4user phones







System parameters	
Operation system	Embedded Linux Operation System
Mobile App Requirement	Android/IOS
Motion Sensor	With motion dectection function
Detection range	5M/90degrees
On line visitor	Support up to 4 user phones
DDNS	Only connect by P2P service
Camera parameters	
lmage sensor	CMOS 720P Colorful Camera
Light sensitivity	Support Night vision
Lens	2.2mm, Field of view: 125° (Horizontal), 100° (Vertical)
Video parameters	
Video compression standard	H.264
Resolution & frame rate	720P
Sensor support options	AWB AGC, IR filter and BLC
Video Bit Rate	128kbps ~ 1024kbps
Audio parameters	
Audio streaming	Two-Way
Audio input/out	Built-in Omnidirectional Microphone/Loudspeaker
Audio quality	Noise Suppression and Echo Cancellation
NETWORK/Interface	
Network protocol	TCP/IP
WiFi	802.11b/g/n
Network security	WPA,WPA2
Wireless Connection	STA/Pairing Mode
Motion Detection	Yes
Remote unlock	Yes, Unlock your door via APP
WiFi Distance	<80m
Reset Button	Yes
GENERAL	
Ingress protection level	IP 55
Power supply	AC/DC 8-36V
Power consumption	Max. 3 W
Working temperature	-20° C to +60° C (-4° F to 140° F)
Working humidity	10% to 90%
Dimensions	68 mm x 140 mm x 25 mm (2.7" x 5.5" x 1.0")

©2017 LT Security, Inc. All Rights Reserved. White papers, data sheets, quick start guides, and/or user manuals are for reference only and may or may not be entirely up to date or accurate based upon the version or models. Product names mentioned herein may be the unregistered and/or registered trademarks of their respective owners.









