

Hot Air SMD Rework Soldering Station SR-979



Product Description

Hot Air SMD Rework Station, SMD Rework Soldering Stationn

The hot air SMD rework station SR-979 is engineered to meet the demanding needs of today's electronic industry, technicians, service / repair and assembly rework. The system not only increase productivity for SMD assembly and repair but achieves a new standard of quality in partnership with "Hot Air SR-979" superior performance and easy of operation.

Hot Air Rework Stations SR-979: Welding

This hot air rework station will highly regulate the air flow and the temperature and is available for QFP and SOP ICs. Both the welding and the descaling shall be conducted with the same nozzle.

The auto removal of static electricity offers more safety to the elements and the operation, different ICs would be regulated to different temperatures.

SMD Rework Stations SR-979: Auto Cooling system

After turning off the power, the auto cooling system remains operational, just to keep the service life of the heating elements and the handle.

SMD Rework Soldering Station SR-979

The SMD rework soldering station SR-979 is applicable for galvanized welding and removal of QFP and SOP ICs and it is applicable for telescopic hoses.

Keep the nozzle in use and the element duly spaced, for protection of the elements.

Special design of welding and removal of PLCC flat below IC.

Product Specifications

Voltage	110/120V AC or 220/240 V AC
Power consumption	275W
Hot Air Temperature	100°C~400°C 212°F~754°F
Handpiece	235mm
Station	L247:W190:H135 (mm)
Weight	4500g
Station-Handpiece cordlength	110 cm
AC Power cord	3 cored (with 3pin plug 180cm)
Packing Measure	4 pcs CUFT 2.12'



Optional Parts

